

## WORLD'S BEST AND NO. 1

High Performance Surface Protection Film

### ARGUMENTS, QUESTIONS, WARRANTIES AND MAINTENANCE

#### Arguments

- **Argument 1:** Omega-Shield™ stone chip protection film creates a crystal-clear invisible barrier between the car paint and the outside world. This way, the paintwork underneath the film remains in showroom condition for years, as if the car had just rolled out of the showroom.
- **Argument 2:** Omega-Shield™ prevents scratches in the paint when the vehicle goes through a car wash.
- **Argument 3:** Omega-Shield™ has the same high gloss level as automotive paint. This makes it virtually invisible. But even more important: in certain zones the paint simply cannot be damaged. And that's what matters. Omega-Shield™ is resilient and absorbs every impact on the paintwork, such as flying gravel, branches and desert sand.
- **Argument 4:** The vehicle retains a higher (trade-in) value because the paint is still in showroom condition.
- **Argument 5:** 90% of common paint damages are prevented with Omega-Shield™.
- **Argument 6:** Is Omega-Shield™ expensive? What is better: having to respray a bumper, hood, fender or mirrors at high cost, with the risk of color difference, plus losing the original factory paint... or having Omega-Shield™ film installed once and then enjoy 10 years of carefree driving without paint damage?
- **Argument 7:** Okay, you have your car paint repaired and resprayed because of stone chips or paint damage. Cost: at least 2000 euros. You haven't even driven 10,000 km and you already have new stone chip damage because you drove behind a truck... Avoid this! People who already had Omega-Shield™ installed are still driving carefree today; without any paint damage!

#### Frequently Asked Questions

- **Question 1:** **Does the film have a negative effect on the car paint?**  
No! Omega-Shield™ protects your car against paint damage and keeps it in showroom condition year after year, while the film remains virtually invisible.
- **Question 2:** **Can Omega-Shield™ films be waxed?**  
Yes, you can wash and wax your car as if Omega-Shield™ was not there. Use synthetic wax types only. Natural waxes containing Carnauba are a no-go.
- **Question 3:** **Will the paint of a car eventually fade under the sun?**  
Yes, every paint will. Omega-Shield™ film is UV-stable and does not discolor, but UV radiation is transmitted. This is done deliberately, so that both the paint under the film and the unprotected paint keep the same color.
- **Question 4:** **Can Omega-Shield™ film be removed again?**  
Yes. Omega-Shield™ has a patented acrylic adhesive layer that can be safely removed even years after application, without leaving residue and without affecting the paint.
- **Question 5:** **Can Omega-Shield™ film be installed by yourself?**  
To obtain 100% invisible, crystal-clear paint protection, an installer recognized by us is required. This installer has followed professional training with us. Use our website with recognized dealers and installation companies to find a professional near you.
- **Question 6:** **How do you remove stains from the film?**  
See the maintenance guidelines on the back of this sheet.

## WORLD'S BEST AND NO. 1

### High Performance Surface Protection Film

## ARGUMENTS, QUESTIONS, WARRANTIES AND MAINTENANCE

### Warranty

- Omega-Shield™ GLOSS has a lifetime warranty\*. This applies from the installation date on a specific vehicle and as long as it remains in the possession of the same owner. Otherwise, the warranty/lifespan is 10 years. All other Omega-Shield™ products have a warranty of 5–7 years. Both are non-transferable.
- Omega-Skinz® warrants Omega-Shield™ Automotive Paint Protection Film against discoloration, fading, cracking or bubbling. The warranty is valid as long as the installation is carried out according to the manufacturer's recommended installation procedures and is not transferable. The warranty is limited to replacement of defective material.
- The warranty does not cover defects and consequential damages that are directly or indirectly caused by incorrect installation such as lifting, air bubbles, streaks/smudges or misalignment. This warranty also does not apply to damage to the product or substrate resulting from improper application, incorrect surface preparation, accidental or negligent misuse, exposure to corrosive or abrasive materials, or direct impact from road debris. If the Omega-Shield™ film fails to meet the warranty requirements during the usage period, the purchaser may have the film replaced or repaired at any authorized Omega-Shield™ Dealer or Installer worldwide. The manufacturer's obligation under this warranty is limited to replacement of defective film; liability shall not exceed the purchase price of the film. Proof of purchase will be required by the authorized installer to support any warranty claim.
- Any purchaser wishing to make a warranty claim must first contact the original installer before contacting the importer or manufacturer. Visit our website to find your local authorized Omega-Shield™ Dealer or Installer.
- Proof of purchase, together with the warranty card, is required to qualify for warranty.
- Exclusivity: This warranty is exclusive and replaces all other warranties, express or implied, including but not limited to warranties of merchantability and/or fitness for a particular purpose. All other warranties, except those expressly set forth above, are expressly excluded. The warranties mentioned herein are the sole and complete warranties, and no waivers, additions, or modifications to the foregoing terms are valid unless made in writing and signed by an Omega-Skinz™ sales manager.
- Limitations: Some jurisdictions do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations may not apply to you. Except where prohibited by law, Omega-Shield™ and the authorized Omega-Shield™ Dealer or Installer are not liable for any damages arising out of or related to the product, whether direct, indirect, incidental or consequential, regardless of the alleged legal theory. This warranty gives you specific legal rights. The product must be used in accordance with and in compliance with all applicable state or provincial laws. Installation of this product in a way that violates state or provincial laws, or interferes with the operation of the vehicle, is considered misuse of the product and voids all warranties.
- **NOTE:** This warranty does not apply to vehicles used on a racetrack, fleet, courier, livery, rental or other commercial applications for profit.

#### \*Lifetime warranty

*Omega-Shield™ GLOSS comes with a lifetime warranty. This applies from the installation date on a specific vehicle (car or motorcycle) and for as long as it remains in the possession of the same owner. The installation must also have been carried out by a manufacturer-authorized installer. Otherwise, the warranty/lifespan is 10 years. All other Omega-Shield products carry a warranty of 5–7 years. Both are non-transferable.*

### Maintenance

- **Note:** The applied film must cure for at least 48 hours before it can be washed or undergo any similar treatment. This allows the pressure-sensitive adhesive layer to fully cure and the moisture to completely evaporate. After 48 hours have passed, follow the simple maintenance instructions below:
- Use a clean microfiber cloth or chamois to treat your Omega-Shield™ film only with synthetic wax. Do not use natural wax (e.g., Carnauba)! Also avoid colored types of car wax. Use only white or clear synthetic wax.
- **Interim cleaning**  
Always wash off contaminants (insects, bird droppings, etc.) immediately. If left on the film for an extended period, stains may occur, just as the acids would eventually attack your valuable car paint.
- **Washing/rinsing**  
Wash your vehicle as usual. When using a high-pressure cleaner, the nozzle must be kept at least 1 meter away from the edges of the film to prevent peeling. Never aim the nozzle directly at the film edges; the powerful jet can damage the film.
- **Drying**  
To dry the film, use a normal microfiber cloth or blow off the excess water with a wet/dry vacuum.
- **Cleaning the film edges**  
Wax and dust may accumulate at the film edges. For cleaning, use a regular cotton swab dipped in 70% isopropyl alcohol (IPA or rubbing alcohol) and wipe away from the edge, never towards it.
- **Avoid using...**  
Do not use solvent-based cleaners, insect removers or degreasers, abrasives or other scouring materials. Polishing equipment may be used, but only at low speed and with minimal force. We recommend performing a test on a small section of the bumper before using it on the hood or fenders.

Your dealer:

